



SORAA 7.5W LED MR16 3000K VIVID3 25° DIM

Item #777058

Ordering Code SM16-07-25D-930-03

UPC 849565009352

- Works with trailing edge and leading edge phase cut dimmers
- Enclosed fixture compatibility allows operation in damp or outdoor locations
- White point accuracy within 3 SDCM
- CUL rated for 12VAC NEC Class 1 and Class 2 systems
- SORAA SNAP SYSTEM compatible with spot models
- VIVID lamps offer excellent color rendering: CRI = 95 & R9 = 95
- 7.5W LED = 50W HALOGEN
- \*Energy Star Qualified



## TECHNICAL SPECIFICATIONS

Item #	Watts	Bulb Type	Base	Volts	Finish/Description	Beam Angle (°)	Color Temperature (CCT)	
777058	7.5	MR16	GU5.3	12	N/A	25	3000K	
Color	CRI	Lumens	CBCP	Average Hours	M.O.L. (inches)	M.O.D. (inches)	Incandescent Equivalent	
Soft White Light	95	435	2400	35000	1.875	2.000	50W	
Energy Star	DLC	Title 24 Compliant	Safety Rated	Safety Rating	Type Enclosed	Rated	Dimmable	Warranty
N	N	Y	UL	DAMP	Y	Y	Y	3

Order Multiple  
QTY  
10

## APPLICATION SUGGESTIONS



Landscape



Recessed



Track

