



SM16 VIVID WARM DIM MR16 / 12V 7.5W / 3000K to 1800K / 36°

Item #777836

Ordering Code SM16-07-36DM-930/918-01

UPC 84956506625

- Warm dimming capabilities give designers flexibility to create warmer, more intimate environments
- Color point mimics halogen from either 3000K or 2700K to 1800K, while 95 CRI and 95 R9 are maintained throughout the dimming range.
- 85% more energy efficient than standard halogen lamps
- Intended for use in MR16 compatible recessed downlights, track lighting and other indoor and outdoor applications
- Suitable for damp locations
- Works with trailing edge and leading-edge phase cut dimmers
- Automatic safety shut down in any thermal environment not conducive to minimum airflow or proper ventilation
- Whiteness methodology matches or exceeds that of halogen and incandescent sources at 2700K and 3000K.
- CUL rated for 12VAC NEC Class 1 and Class 2 systems
- 7.5W LED = 50W HALOGEN



TECHNICAL SPECIFICATIONS

| | | | | | | | |
|------------------|-------|--------------------|--------------|--------------------|--------------------|-----------------|-------------------------|
| Item # | Watts | Bulb Type | Base | Volts | Finish/Description | Beam Angle (°) | Color Temperature (CCT) |
| 777836 | 7.5 | MR16 | GU5.3 | 12 | Clear | 36 | 3000K |
| Color | CRI | Lumens | CBCP | Average Hours | M.O.L. (inches) | M.O.D. (inches) | Incandescent Equivalent |
| Soft White Light | 95 | 430 | 1030 | 25000 | 1.79 | 1.97 | 50 |
| Energy Star | DLC | Title 24 Compliant | Safety Rated | Safety Rating Type | Enclosed Rated | Dimmable | Warranty |
| N | N | N | UL | DAMP | Y | Y | 3 |

Order Multiple
QTY
1

