



Cimarron® Comfort Height®

Elongated chair height toilet bowl
K-5309

Features

- Elongated bowl offers added room and comfort.
- Skirted trapway simplifies cleaning.
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults.
- 2-1/8-inch fully glazed trapway.
- Patented ReadyLock™ installation system is a simple solution for Skirted toilets that saves time, hassle and eliminates the need to drill into the floor for a standard 12" rough in.
- Combines with the K-4369/4369-RA tank to create a complete K-5310/5310-RA Cimarron toilet.
- Coordinates with other products in the Cimarron collection.

Installation

- Standard 12-inch rough-in (10- and 14-inch rough-in kits also available).
- Seat and supply line not included.

Recommended Products/Accessories

K-4369 Toilet tank, 1.28 gpf

Included Components

Additional Components:
Floor Mounting Kit



ADA **CSA B651** **OBC**

Codes/Standards








ASME A112.19.2/CSA B45.1
DOE - Energy Policy Act 1992
California Energy Commission (CEC)
ADA
ICC/ANSI A117.1
CSA B651
OBC

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	7	Black Black™



Cimarron® Comfort Height®

Elongated chair height toilet bowl

K-5309

No image available.

This product is a component and not intended to be a standalone installation.

Technical Information

All product dimensions are nominal.

Toilet type:	Two-piece
Trap passageway:	2-1/8" (54 mm)
Rough-in:	12" (305 mm)

Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.