

Inspired by the profile of modern lever door hardware, the sleek Nate outdoor wall sconce reflects LED light off the wall to create a perfect grazing light effect on architectural surfaces—either indoors or outside. Cleverly hidden hardware ensures a clean look.

### Outstanding protection against the elements:

- Powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

### SPECIFICATIONS

DELIVERED LUMENS	136
WATTS	11
VOLTAGE	120V
DIMMING	ELV
LIGHT DISTRIBUTION	Symmetric
MOUNTING OPTIONS	Wall (Up or Down)
CCT	3000K
CRI	90
COLOR BINNING	3-Step
BUG RATING	N/A
DARK SKY	Compliant
WET LISTED	IP65
GENERAL LISTING	ETL
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	Yes
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Powder Coat
LED LIFETIME	L70; 70,000 hours
WARRANTY*	5 years
WEIGHT	4.5 lbs.

\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.



NATE 17  
shown in bronze




NATE 17  
shown in graphite

### ORDERING INFORMATION

7000WNT	SIZE	FINISH	LAMP
17	17"	Z BRONZE I SILVER	LED930 LED 90CRI, 3000K, 120V

# NATE 17 WALL SCONCE



Nate 17

## PHOTOMETRICS\*

\*For latest photometrics, please visit [www.techlighting.com/OUTDOOR](http://www.techlighting.com/OUTDOOR)

### NATE 17

Total Lumen Output:	136
Total Power:	11
Luminaire Efficacy:	12
Color Temp:	3000K
CRI:	90
BUG Rating:	N/A

## PROJECT INFO

FIXTURE TYPE & QUANTITY	JOB NAME & INFO	NOTES



GENERATION BRANDS  
 7400 Linder Avenue, Skokie, Illinois 60077  
 T 847.410.4400 F 847.410.4500