

## Drake® II Close Coupled Toilet, 1.28GPF

### FEATURES

- Tornado Flush™ system, high-efficiency (1.28GPF/4.8LPF)
- Optional CEFIONTECT® ceramic glaze - prevents debris and mold from sticking to ceramic surfaces, leading to fewer chemicals and less water in cleaning.
- Universal Height
- Decorative two-piece design with high-profile tank
- Elongated front bowl and tank set, less seat
- Chrome trip lever
- 12" Rough-in, supply line sold separately

### MODELS

- CST454CEFG  
With CEFIONTECT ceramic glaze
- CST454CEF  
Without CEFIONTECT ceramic glaze

### COMPONENTS

- C454CUFG Elongated bowl with CEFIONTECT
- C454CUF Elongated bowl, without CEFIONTECT
- ST454E Tank and cover only
- ST454ER Tank and cover only, right-hand trip lever
  
- SS224 SoftClose® seat (sold separately)
- SS214 SoftClose® seat (sold separately)
- SS204 SoftClose® seat (sold separately)
- SS114 SoftClose® seat (sold separately)
- SC534 Commercial seat (sold separately)

### COLORS/FINISHES

- Standard
  - #01 Cotton
  - #03 Bone
  - #11 Colonial White
  - #12 Sedona Beige
  - #51 Ebony (Without CEFIONTECT glaze)

### PRODUCT SPECIFICATION

The Two-piece low consumption Tornado Flush system toilet shall be 1.28GPF/4.8LPF. Toilet shall have optional CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have high-profile tank, elongated front bowl and Chrome trip lever. Toilet shall be TOTO Model CST454CEF \_\_\_\_.



 **Tornado Flush**

 **CEFIONTECT**

### CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), EPA Watersense, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- ADA compliant (when installed with trip lever located on the approach side)
- Complies with CA Prop 65 warning requirements



# CST454CEF(R)(G)

## Drake® II Close Coupled Toilet, 1.28GPF


### SPECIFICATIONS

- Water Use 1.28 GPF/4.8LPF
- Flush System Tornado Flush™
- Min. Water Pressure 8 psi (static)
- Water Surface 7-1/8" x 9-1/8"
- Trap Diameter 2-1/8"
- Rough-in 12"
- Trap Seal 2-1/8"
- Warranty One Year Limited Warranty
- Material Vitreous china
- Shipping Weight C454CUF(G) 57.3lbs.  
ST454E(R) 31.5lbs.
- Shipping Dimensions C454CUF(G)  
29" L X 14-3/4" W1 X  
11-1/2" W2 X 16-1/4" H  
  
ST454E(R)  
18" L X 9" W X 16" H


### INSTALLATION NOTES

#### Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.



**TOTO**

*These dimensions and specifications are subject to change without notice*